



Minivet

1000 - 2000 VA UPS

From The Leading Japanese UPS Company

Applications

Wi-Fi Routers | CCTV System | Servers | Computers | Modems

Technical Specification

Model	Minivet 1000 LB	Minivet 2000 LB	Indicators	
Capacity	1000VA/600W	2000 VA/1200W	AC Mode	Green Lighting
Input			Battery Mode	Yellow Flashing
Voltage	220/230 VAC		Fault	Red Lighting
Voltage Range	140-300 VAC		Alarm	
Frequency Range	50 Hz		Low Battery	Sounds Every Second
Output			Overload	Sounds Every 0.5 Second
AC Voltage Regulation (Batt. Mode)	±10%		Fault	Continuous Sound
Frequency Range (Batt. Mode)	50 Hz ±1 Hz		Protection	
Transfer Time	Typical 4-8 ms		Full Protection	Overload, Discharge and Overcharge Protection
Waveform (Batt. Mode)	Simulated Sine Wave		Physical	
Battery			Dimension, D X W X H (mm)	395 x 145 x 220
Battery Connection	External		Net Weight (kgs)	9 13
No of Battery	12V, 1 Nos	12V, 2 Nos	Standards	
Charging Current	20 A (Settable)	20 A (Settable)	Certifications / Compliances	BIS, CE, IS 16242 (Part 1):2014 IEC 62040-1 : 2008, ISO 9001:2015, ISO 14001:2015, ISO 45001:2018
Battery Capacity used	upto 200AH	upto 200AH	Environment	
Typical Recharge Time	6 - 8 hours upto 90% capacity		Humidity	0-90 % RH @ 0-40°C (Non-Condensing)
			Noise Level	Less than 40dB

Fuji Electric India Pvt. Ltd.